



**Communications Recording Systems,  
Voice Logging Recorders, and Audio Products**  
Serving the Public Service Sector Since 1967

## AP-8X



### Features:

- Designed for military, intelligence, and communications monitoring applications
- Individual Left and Right Headphone Input select and Volume Controls
- Internal Speaker with Input select and Volume Control
- Input connectors will be BNC, 600 ohm
- 3.5" x 19" Rack mounting chassis





**Audio Panel (AP-8X) Specifications**

<b>Audio Inputs</b>	8, Switchable balanced or unbalanced
<b>Audio Outputs</b>	8, Switchable balanced or unbalanced
<b>Connectors</b>	Terminal Strips
<b>Speaker</b>	1 ea. Front mounted 3.0' 8 OHM
<b>Power and THD</b>	.5 watts, .03% THD
<b>Headphone Jacks</b>	2 ea. For 600 OHM stereo headphones
<b>Headphone power and THD</b>	.3 watt, .01% THD
<b>Size and Mounting</b>	3.5 by 19 inch Rack mount, 5 inch deep
<b>Power</b>	115/230 Volts AC, 50/60 Hz, user selectable, 20 watts poer consumption, U.S. Power cord standard. Foreign Power Cord Sets Available, including European <i>Schuko</i> Plugs

2006-11-12